

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2004 (06.05.2004)

PCT

(10) International Publication Number
WO 2004/038171 A1

(51) International Patent Classification⁷: **E21B 29/04**

(21) International Application Number:
PCT/DK2002/000708

(22) International Filing Date: 24 October 2002 (24.10.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): WELL-
TEC APS [DK/DK]; 19, Hejrevej, DK-3450 Allerød (DK).

(72) Inventor; and

(75) Inventor/Applicant (for US only): HALLUNDBAEK,
Jørgen [DK/DK]; 15, Haregabsvej, DK-3230 Graested
(DK).

(74) Agent: CHAS. HUDE A/S; 33 H.C. Andersens Boul-
vard, DK-1780 Copenhagen V (DK).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette

(54) Title: METHOD FOR RELEASING CABLES FROM AN ATTACHED WELL TOOL AND APPARATUS FOR EXERCIS-
ING THE METHOD



(57) Abstract: In a method for releasing
cables (2) from an attached well tool,
where the cutting and the time for cutting
can be decided from the surface above
the well, and where a cable cutter (6)
is arranged between the main part of a
cable and a well tool, said cable cutter
being controlled by a timer, it is suggested
that at least three parameters are used
for controlling the cutter, e.g. a pulling
force exerted by the cable on the well
tool, the pressure in the well location,
and time, where the timer (1) is working
electronically.

WO 2004/038171 A1